EHRLE Terminal-Series



WashTerminal DUO - Self-service car wash for 2-wash bays electrically or gas-heated



Description:

- Self-service car wash two wash bays
- Self-supporting stainless steel outdoor housing
- CC-talk electronic coin validator for cash and tokens
- Option for payment with credit card system
- LED display for remaining amount of money
- SoftFoam generator for SoftFoam INEX | PLUS | XP
- Micro powder dosing system for APPMP
- Liquid dosing for paint protection UltraProtection
- Liquid dosing for gloss drying SuperFinish
- Ionic water softener 1x80m3/dH with salt tank
- Reverse osmosis 7,200l/da for spotless drying results
- Osmosis water storage tank 400 litres with level control
- Frost protection device with internal frost protection WAB

Electrically heated:

Gas heated:

- - LCE Boiler stainless steel 60l LCG stainless gas heating system
- 36kW electric heating system LCE stainless gas heaing system

 - LAS Flue gas system

Technical data	Variant: Electrically heated	Variant: Gas heated
Voltage	1/N/PE/AC/50Hz/230V	
Operating Pressure	130bar/13MPa	
Max. Pressure	150bar/15MPa	
Discharge Capacity	660l/h - 12l/min	
Connected load	42,0kW	9,0kW
Electrical protection	3x63A	3x20A

2-system variants - Application programmes

System variant: with SoftFoam lance (SV4)



Application 1:

PRE-CLEANING (SV4) with soft foam



Application 2:

CLEANING with ActivePower Pearl **MicroPowder High Pressure**



Application 3:

RINSING with clear water



Application 4:

PROTECTION with UltraProtection

with SuperFinish



Application 5: **HIGH GLOSS** System variant: with SoftFoam brush (SV5)



Application 1:

PRE-CLEANING (SV5) with soft foam



Application 2:

CLEANING with ActivePower Pearl **MicroPowder High Pressure**



Application 3:

RINSING with clear water



Application 4: **PROTECTION** with UltraProtection



Application 5: **HIGH GLOSS** with SuperFinish

















